

Product type designation

SpliT Connect Terminator (non-Ex)
PROFIBUS PA SPLITCONNECT TERMINATOR, FOR
TERMINATING OF PROFIBUS PA SEGMENTS, NOT SUITABLE
FOR APPLICATION IN EX-AREA, PACK. UNIT: 5 PIECES PER
PACK



Electrical data

Transfer rate / with PROFIBUS PA	31.25 kbit/s
----------------------------------	--------------

Permitted ambient conditions

Ambient temperature	
• during operation	-40 ... +85 °C
• during storage	-40 ... +85 °C
• during transport	-40 ... +85 °C

Protection class IP	IP67
---------------------	------

Further Information / Internet Links

Internet-Link

- | | |
|---------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| • to website: Selector SIMATIC NET SELECTION TOOL | http://www.siemens.com/snst |
| • to website: Industrial communication | http://www.siemens.com/simatic-net |
| • to website: Industry Mall | https://mall.industry.siemens.com |
| • to website: Information and Download Center | http://www.siemens.com/industry/infocenter |
| • to website: Image database | http://automation.siemens.com/bilddb |
| • to website: CAx Download Manager | http://www.siemens.com/cax |

- to website: Industry Online Support

<https://support.industry.siemens.com>

last modified:

07/07/2016